

Rec'd PCT/PTO

JAN 2005

10/523068

17/05 2003 / 0040 6:8



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QB

REC'D 11 NOV 2003

WIPO

PCT

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

BEST AVAILABLE COPY

Signed

P. Mahoney

Dated

26 September 2003



175EP02 E748783-2 002819
P01/7700 0000-0221512.7

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

C860/H

2. Patent application number

(The Patent Office will fill in this part)

0221512.7

17 SEP 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

John Herbert NORTH
21 Briar Court
Guardian Road
Norwich
NR5 8PR

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

7482763001

4. Title of the invention

Improved separation apparatus

5. Name of your agent (if you have one)

Keith W Nash & Co

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

90-92 Regent Street
Cambridge
CB2 1DP

Patents ADP number (if you know it)

1206001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

No

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 5 

Claim(s)

Abstract

Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)


Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 16/09/2002


Keith W Nash & Co., Agents

12. Name and daytime telephone number of person to contact in the United Kingdom

Keith Nash 01223 355477

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

C860/H

Title: Improved separation apparatus

Field of invention

This invention concerns apparatus using centrifugal force for separating material based on density.

Background to the invention

Whilst conventionally the technique is employed for separating dust and dirt particles from air, the technique is equally applicable to separating one fluid from another such as a liquid from a gas (or air) or one gas from another of different density.

GB Patent Specification 2,367,774 describes a multi-cyclone separation apparatus primarily designed to separate dust and dirt particles from an incoming airstream. One of the cyclone separation zones is contained within chambers 40 and 38, and in Fig 3 the transition from the cylindrical vortex starting chamber 40 to the frusto-conical chamber 38 is effected by a shallow intermediate frusto-conical section 64, having a different cone angle from that of the chamber 38. The reduction in radius of the helical airflow as it progresses down 38 accelerates the airflow in the cyclone as it continues to rotate around and down this section. After exiting therefrom the more dense material separates therefrom and remains in the dust-collecting chamber within the valve seating 80 above the valve closure 74.

The sudden lack of constraint on the airflow (and particularly on higher density content thereof) immediately below the opening at the lower end of cyclone chamber 38, results in a very efficient separation of the higher density content from the lower density content of the air leaving 38. Cyclonic inversion occurs as the rotating air interacts inter alia with the

cup 78, which results in a tightly circulating and upwardly rising helical airflow axially through the lower open end of 38 to travel upwardly and exit through openings 62 in the wall of central vortex-starter tube 58, to pass to the suction producing device 10 (typically a motor driven fan) via a filter 16.

The intermediate section 64 was originally proposed to smooth the transition between the two chambers 40 and 38. However, following experimental work on separators employing such intermediate sections it has become evident that the intermediate frusto-conical transition section has other advantages not hitherto appreciated, and the present invention identifies these alternative uses for an intermediate frusto-conical transition region between these two chambers.

Summary of invention

According to one aspect of the present invention in a cyclonic separation apparatus comprising a cylindrical vortex-starting chamber and frusto-conical main cyclonic separation chamber, an intermediate frusto-conical region is provided at the entrance to the main frusto-conical cyclone chamber for the purpose of reducing the overall axial length of the two chambers, thereby enabling a cyclonic separating vacuum cleaner to be built of reduced overall height for a given separation efficiency.

In particular the use of an intermediate frusto-conical region such as 64 has allowed the overall height of the two chambers (38, 40) making up the second cyclone separation stage of a two-stage cyclone separator, to be reduced.

A similar height reduction could be obtained if the lower end of chamber 40 is flat and perpendicular to the axis of 40 around the entrance to the frusto-conical chamber 38, but the turbulence created by such an arrangement dramatically reduces the separation efficiency of the cyclone system relative to what has been found when using an intermediate frusto-conical region between the cylindrical vortex-starting chamber and the main frusto-conical cyclonic separation chamber.

Experiments have also revealed that for a range of cone angles for the intermediate frusto-conical region, the separation efficiency is greater than if the main lower frusto-conical region were to be continued upwardly at the same cone angle, until its diameter corresponds to that of chamber 40 (thereby obviating any intermediate transition of any form) as in Fig 18 of GB 2,367,774 or in the separator shown in Figs 1 and 2 of EP 0042723, or Fig 5 of GB 2,321,181. Therefore not only is the overall height of the two chambers 38, 40 significantly increased if no intermediate frusto-conical transition section is employed, but the separation efficiency of the unit has been found to be less than that of a unit having an intermediate frusto-conical transition section 64.

According to a second aspect of the present invention in a cyclonic separation apparatus comprising a cylindrical vortex starting chamber and frusto-conical main cyclonic separating chamber, the transition between the cylindrical vortex starting chamber and the main frusto-conical cyclone defining separation chamber is located in the region of the downstream end of a central tubular member which extends axially of the vortex starting chamber, and is formed by an intermediate frusto-conical region having a larger cone-angle than that of the main cyclone chamber.

With reference to Fig 3 of GB 2,367,774, by locating the intermediate frusto-conical wall section 64 in the region of the apertured lower end of the central vortex starting tubular housing 58, a rapid reduction in radius is forced on the descending helical airflow which is accompanied by a corresponding rapid increase in rotational velocity in the region of the exit apertures 62 and just before it enters the conventional longer cyclone section 38.

A more rapid increase in rotational velocity near the apertures 62 in the end of tube 58 has been found to more successfully retain higher density content in the rotating airflow as it transfers to the main cyclone chamber 38, than if no such intermediate frusto-conical section is employed, as in the embodiment of Fig 18 of GB 2,367,774. This means less chance of higher density material migrating radially inwardly to exit via the apertures 62 instead of remaining in the airstream and travelling therein to the far end of the main

cyclone chamber 38 to be separated from the airflow and left in the collection zone, beyond 38.

This improvement has become even more noticeable when employing the apparatus to separate liquid from an incoming airstream.

In a preferred embodiment the half cone angle of the main frusto-conical section of the cyclone separator is in the range 8° to 14° , preferably 10° to 12° , while that of the intermediate frusto-conical section of the separator is in the range 20° to 40° , preferably 32° to 34° .

Two particularly preferred combinations of half-cone angles are 34° and 10° , and 32° and 12° respectively.

According to a third aspect of the present invention by incorporating an intermediate frusto-conical section between a cylindrical vortex starting chamber and a main frusto-conical cyclone chamber, thereby reducing the overall axial length of the two chambers, the main cyclone chamber can be mounted so as to extend to a lesser axial extent into a main dust collecting bin than would otherwise be the case, without increasing the combined axial length of the two chambers and the bin, thereby effectively increasing the volume of the bin available for storing dust and dirt, for a given combined axial length.

Where the apparatus is adapted to separate liquid from air, it is very advantageous to provide the maximum volume for collecting liquid in the bin (in place of dirt and dust particles) and as mentioned above the intermediate frusto-conical region provided for the purpose of increasing this volume is also found to improve the separation of water droplets from the airstream in the second cyclone set up by the cylindrical starter chamber and which thereafter helically rotates axially through the main cyclone chamber.

Definition of cone angle

In general the present invention only relates to shapes which are regular cones or frustums of regular cones.

If a regular cone is cut to reveal a triangular section, the cone angle is the angle between the two converging sides of the triangular cross-section which intersect at the apex of the cone. The axis of the regular cone bisects the cone angle, and each half of the cone angle is referred to herein as a half-cone angle. The cone angle of a frusto-conical shape is the cone angle of the regular cone which would be formed if the frusto-conical shape is continued to form a cone.

Results of experiments

Experiments have been undertaken using apparatus employing an intermediate frusto-conical region such as shown in Fig 3 of GB 2,367,774, in which the internal diameter of the cylindrical chamber 40 is 65mm, the half-cone angle of the intermediate frusto-conical section is 34° , and that of the longer main section 38 is 10° , the diameter of the smaller open end of the main section 38 is 18mm, and a gap of the order of 7 to 8mm is provided between the 18mm diameter opening and the plate 78 (see Fig 4 of GB 2,367,774).

With an airflow rate of 41-42 litres per second at inlet 14, between 0.5 and 1gm of Kaolin was found in the final filter from a 200gm charge of Kaolin introduced into the airflow. Typically 190-191 grams of Kaolin was found in the dust-collecting bin and between 8 and 9 grams in the cyclone system after the experiments.

In the case of 1 litre of water introduced into the airstream at the dirty air inlet such as 14 of Fig 3 of GB 2,367,774, with a similar air flow in the range 41-42 litres per second, the weight of water not collected in the bin at the end of the experiment (i.e. lost during separation) was of the order of 0.02gm. This equates to the evaporative loss expected from the mixing of 1 litre of water at room temperature with an airflow of 41-42 litres of air per second at the same temperature.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.